

COLORS:	HEMSBY HILLWOOD ALDIN BARNSELEY	COLEMAN CAMPTON SUTTON WELFORD	WINSLOW BOWDEN
DIMENSIONS:	3/4" X 9-1/2" X 23" - 96" (84% full): HEMSBY, HILLWOOD 25/32" X 9-1/2" X 23" - 96" (84% full): ALDIN, BARNSELEY, COLEMAN, CAMPTON, SUTTON, WELFORD, WINSLOW, BOWDEN		
SPECIES:	EUROPEAN OAK		
FINISH:	BONA® UV URETHANE FINISH		
GLOSS LEVEL:	ULTRA-MATTE		
GRADE:	COUNTRY		
TREATMENT:	SMOKED + REACTIVE: HEMSBY, WALDEN, COLEMAN REACTIVE: HILLWOOD, CAMPTON, EATON, SUTTON, BARNSELEY, WELFORD, ALDIN, WINSLOW		
TEXTURE:	WIRE BRUSHED: HEMSBY, WALDEN, HILLWOOD, BOWDEN SMOOTH: CAMPTON, SUTTON, BARNSELEY, WELFORD, ALDIN, WINSLOW, COLEMAN		
EDGES:	MICRO-BEVELED		
TOP LAYER:	DRY-SAWN, 6MM THICK		
CORE:	HARDWOOD LUMBER (HEVEA)		
PROFILING:	TONGUE & GROOVE FOUR SIDES (END-MATCHED)		
ADHESIVE:	EPI, FORMALDEHYDE-FREE PRODUCT CONTAINS NO ADDED FORMALDEHYDE (NAF, NAUF) CARB ATCM PHASE II / EPA TSCA COMPLIANT (<0.05PPM)		
FSC-CERTIFIED:	FSC AVAILABLE BY SPECIAL ORDER		
WARRANTIES:	STRUCTURAL – LIFETIME FINISH – 25-YR RESIDENTIAL/3-YR LIGHT COMMERCIAL WHEN PROPERLY MAINTAINED PER CARE & MAINTENANCE INSTRUCTIONS NOT APPROVED FOR USE OVER RADIANT HEAT SYSTEMS DUE TO LARGE PLANK SIZE		
INSTALLATION METHOD:	GLUE-DOWN, NAIL + GLUE, OR FLOAT		
CERTIFICATION:	FLOORSCORE CERTIFIED BY SCS GLOBAL SERVICES		